Cox Business® Connect with RingCentral Available Devices

The following devices are available for purchase to use with the Connect with RingCentral packages.

Poly Edge Series Phones



E220

- Four (4) line keys for presence monitoring
- Integrated Bluetooth® 5.0 for mobile phone or headset pairing
- Bright 2.8" color IPS LCD display
- Integrated PoE support





E350

- Eight (8) line keys for presence monitoring
- Integrated Bluetooth® 5.0 for mobile phone or headset pairing
- Bright 3.5" color IPS LCD display
- Text-to-speech and accessibility options
- Built-in WiFi
- Integrated PoE support





E450

- Eight (8) line keys across dual displays
- Two color IPS LCD displays
- Integrated Bluetooth® 5.0 for mobile phone or headset pairing
- Text-to-speech and accessibility options
- Integrated PoE support





E550

- 12 line keys supporting up to 48 lines for presence monitoring
- Integrated Bluetooth® 5.0 for mobile phone or headset pairing
- Large 5" color IPS LCD display
- Text-to-speech and antimicrobial protection
- Integrated PoE support





Poly CCX Series Phones



CCX 400

- Entry level business phone
- 5" multi-touch color LCD display
- Poly Acoustic Fence technology to reduce background noise
- One USB port (Type A) to connect a headset
- Integrated PoE support



CCX 500

- Mid-range business phone
- 5" multi-touch color LCD display
- Poly Acoustic Fence technology to reduce background noise
- NoiseBlock Al
- Built-in Bluetooth and two USB ports [(1) Type A, (1) Type C] to connect a headset
- Integrated PoE support



CCX 600

- Performance business phone
- 7" multi-touch LCD display
- Make video calls from your phone with EagleEye Mini USB camera (not included)
- Built-in WiFi and Bluetooth
- Two USB ports [(1) Type A, (1) Type C] to connect a headset
- Integrated PoE support



CCX 700

- Video desk phone
- 7" multi-touch LCD display
- Make video calls from your phone with integrated 4 megapixel camera
- Hear every nuance with award-winning Poly audio technology
- Built-in WiFi and Bluetooth
- Powerful chipsets support next-generation features such as NoiseBlock AI
- Two (2) USB ports [(1) Type A, (1) Type C] to connect a headset
- Integrated PoE support



Cisco CP Series Phones



CP6821

- Two-line IP phone
- Ideal for common areas
- 132 × 64 pixel monochrome backlit display
- Two (2) line keys for presence monitoring
- Dedicated RJ-9 headset port
- In-call keys: call transfer and hold
- Wideband audio
- Two (2), 10/100 Ethernet ports
- Integrated PoE support



CP7841

- Cost-effective, energyefficient phone
- Up to four (4) lines with programmable line keys
- Backlit 3.5", 396 × 162 pixel graphical display
- Fixed function keys for messaging, directory, hold/resume, transfer, and conference features
- Dedicated RJ-9 headset port
- Two (2) integrated, gigabit Ethernet ports
- Integrated PoE support





CP8851

- Color display IP phone
- 10 line keys with eight (8) line keys dedicated to presence monitoring
- 800 × 480 pixel, 24-bit color,
 5" WVGA display
- Two (2) integrated, gigabit Ethernet ports
- Dedicated RJ-9 headset port
- Integrated PoE support





CP8861

- Advanced phone for knowledge workers
- Up to 10 lines with programmable line keys
- 5", 800×480 pixel, color, backlit, graphical widescreen display
- Dedicated RJ-9 headset port
- Two (2) integrated, gigabit Ethernet ports
- Integrated PoE support





Wireless DECT IP Phones

with Microban® antimicrobial product protection



Rove 20 + B1 DECT Package (up to 4 handsets)

- Wireless DECT IP phone solution with Secure DECT encryption
- HD voice quality
- 2" color display; equipped with a 2" TFT color LCD, with backlight for clear visibility
- Customizable line keys
- Easy-to-Clean Design
- Push-to-talk
- Full-duplex handsfree speakerphone
- Compliant with ADA Section 508
 Subpart B 1194.23





Rove 30 + B2 DECT

- Wireless DECT IP phone solution with Secure DECT encryption
- Supports up to 20 handsets per base,
 20 lines, and 10 simultaneous calls
- Up to 300 hours of standby time and up to 18 hours of talk time
- Ruggedized handsets are drop proof (up to 6.6 ft/2 m), and IP65 dust-tight and water resistant
- HD voice with background noise suppression
- Large 2.4" color HD display



Rove 40 + B2 DECT

- Wireless DECT IP phone solution with Secure DECT encryption
- Supports up to 20 handsets per base,
 20 lines, and 10 simultaneous calls
- Up to 300 hours of standby time and up to 18 hours of talk time
- Ruggedized handsets are drop proof (up to 6.6 ft/2 m), and IP65 dust-tight and water resistant
- HD voice with background noise suppression
- Large 2.4" color HD display
- Dedicated emergency key



Cisco Analog Telephone Adapter (ATA)



Cisco ATA 191

- Compact
- Easy to install
- Two (2) RJ11 ports for analog devices
- One (1) RJ45 Ethernet port for network





Cisco ATA 192

- Compact
- Easy to install
- Two (2) RJ11 ports for analog devices
- Two (2) RJ45 Ethernet ports for network



Poly IP Conference Room Phones



Trio 8300

- Two-line IP phone
- Ideal for common areas
- 132 × 64 pixels monochrome backlit display
- Two (2) line keys
- Dedicated RJ-9 headset port
- In-call keys: call transfer and hold
- Wideband audio
- Two (2), 10/100 Ethernet ports
- Integrated PoE support



Trio 8800

- · Cost-effective, energy-efficient phone
- Up to four (4) lines with programmable line keys
- Backlit 3.5", 396 × 162 pixel graphical display
- Fixed function keys for messaging, directory, hold/resume, transfer, and conference features
- Dedicated RJ-9 headset port
- Integrated Gigabit 2-port Ethernet switch
- Integrated PoE support



Trio C60

- Color display IP phone
- 10 line keys with eight (8) line keys dedicated to presence monitoring
- 800 × 480 pixel, 24-bit color, 5" WVGA display
- Two (2) integrated, gigabit Ethernet ports
- Dedicated RJ-9 headset port
- Integrated PoE support





Phones with Sidecars



Poly Edge E450

- Eight (8) lines
- 66 presets with expansion module





Poly Edge E550

- 12 lines
- 66 presets with one (1) expansion module
- 132 presets with two (2) expansion modules



Cisco IP Phone 8851

- 10 lines
- 56 presets with expansion modules



©2025 RingCentral, Inc. All rights reserved. RingCentral, the RingCentral logo, and all trademarks identified by the ° or ™ symbol are registered trademarks of RingCentral, Inc. Other third-party marks and logos displayed in this document are the trademarks of their respective owners.

©2025 Cox Communications, Inc. All rights reserved. CB-265-241702-01 02/25



